
The New Advantage "Plug and Play" Pond Filter System

The easiest filter to operate is now part of



-Clear top closure lid to verify the bead media is loose during backwashing cycle.

-Electrical Control Tower. The switches located on top of the tower control two of the four plugs below.

-Four plug outlets. The right two outlets are controlled by the switches above. One is used to operate the pump while the other outlet can be used for any optional equipment such as an air pump or lights. The UV light and Blower connect

to the two left outlets. All outlets are GFCI protected.

-Main power supply cord for electrical control system is 12 gauge wire and 20 feet long.

-All plumbing comes precut and glued. Simply assemble the plumbing by screwing the color coded union together.

Six easy steps to a perfect installation every time. (Approximately 30 minutes)

to maximize light efficiency.

1) Set pad on any flat, stable surface.


pump available.

- 2) Place equipment on marked out areas on pad.
- 3) Attach pre-assembled plumbing to equipment.
- 4) Plug pump, blower and UV light into lower box.
- 5) Plug master plug into electical source. (Source should be a 20 amp dedicated circuit)
- 6) Connect waste, suction and return lines to pond. (These three connections must be glued.)

***Your Satisfaction is Guaranteed!**

The Advantage Bead Filters perform so well that it is the only filter on the market today that offers a 1 year "Satisfaction" guarantee. If for any reason, during the first year you are not completely satisfied with any Advantage Filter, Sacramento Koi will gladly buy it back. No questions asked.

Go to our website or call for the free **brochure** "20 Questions To Ask Yourself Before You Build A Koi Pond." If you are building a new pond you need to read this brochure first.



-The Advantage Plug and Play System comes in several sizes for ponds ranging from 1,000 to 15,000 gallons.



(Advantage 15,000 Gallon Plug and Play System)



Advantage 10,000 Plug and Play System

Each piece of equipment chosen is oversized for a 10,000 gallon pond to ensure that you will never outgrow this filter system.

ADVANTAGE



Advantage 15 Bead Filter

- -Recommended for ponds up to 15,000 gallons.
- -Recommended flow rate of 25-80 GPM
- -Maximum pressure of filter tank is 50 PSI
- 1 year "satisfaction guarantee"
- 5 year warranty on tank
- 2 year warranty on blower & multiport valve.
- 2 Hp blower
 - 7.4 amps
 - Used only during backwashing filter.
- Comes complete with Filter Body, Multiport Valve Head, Bead Media, 2 Hp. Blower and clear lid.

Emperor Aquatics UV Light



- -120 watt high output sterilizer
- -Maximum pond size: 13,800 gallons
- -Recommended pond size: 11,520 gallons
- -Recommended flow rate: 64-76 GPM

Advantage Custom Pump

- -1/2 Hp custom pump
- -3 year warrantee
- -Built in leaf trap
- -2 inch threaded in/out

The Water Flow and Power Consumption You Can Expect

Trying to accurately predict the water flow through a filter, UV light and pump combination is extremely complicated without a detailed head pressure performance curve of each piece of equipment. For that reason, Sacramento Koi has tested each compleat Plug & Play Filter System so you can tell beforehand exactly what performance you can expect. All you need to do is estimate how many feet of head pressure your pond has AFTER the filter system (waterfall, jets, etc..). Then, simply refer to the chart below to see what you can expect from each of the pumps offered on this Plug & Play Filter System. (see www.PlugAndPlayFilters.com for more options)

1/2 Hp Advantage Custom Pump

- 73 GPM (4380 GPH) @ 0 ft. of head after the filter.729 watts 68 GPM (4080 GPH) @ 5 ft. of head after the filter.718 watts 63 GPM (3780 GPH) @ 10 ft. of head after the filter.704 watts

2 x 1/3 Hp Artesian Pump in tandem

- 81 GPM (4860 GPH) @ 0 ft. of head after the filter. 973 watts 77 GPM (4620 GPH) @ 5 ft. of head after the filter. 960 watts 72 GPM (4320 GPH) @ 10 ft. of head after the filter. 950 watts

- -Designed for ponds up to 10,000 gallons.
- -Can be installed in as little as 30 minutes.
- -Only three fittings to glue and no electrical to do.



- Equipment Light - \$99
- Digital Timer - \$149 -
- 2nd Electrical Box \$85 -(4 always on outlets)
- Low Voltage Transformer -

(100 watt - \$139) (300 watt - \$159)

Automated Control System w/ Remote - \$765

(Remotely turn on/off 5 seperate outlets. Outlets may also be programed as timer controlled. The 2nd Electrical Box option is included with the Automated Control System providing 3 "always on" outlets.)

Plumbina

- All the plumbing for the Plug & Play is preassembled with unions to make hooking up your new system a breeze. Simply match up colored dots.


Equipment Pad

- 4 feet x 3 feet
- Constructed from heavy duty vinyl

Electrical Control Tower Standard Features

- Two switches
- Four outlets (2 always on, 2 switched)
- GFCI protected
- 20 foot extension cord (12 gauge wire)





А	В	С	D	E	F	G	Н	- 1	J	К	L	М
38 1/8"	26 11/16"	3"	37 ¹ / ₂ "	57 1/2"	52 1/2"	49"	22 1/2"	16"	5 ³ / ₄ "	11 3/4"	15"	43 1/4"

"I" is the measurement for single pump "J" is the measurement for dual pumps